

SPIDER LAMINATED PP SANDTEX R-10 180MIC

Description:

Permanent transparent adhesive. 180MIC PE floor laminate with anti-slip certification.

Applications:

Widely used for floor protection film on printed graphics materials for anti-slip purpose.
The product is mainly suitable for graphic protection; Commonly not for digital printing.

Features:

For the graphic protection.
Eco-Friendly solution for floor graphics.
R10 Anti-slip rating (DIN EN 16165:2023-02 Annex B).

TECHNICAL CHARACTERISTICS	TEST METHOD	AVERAGE VALUE
Thickness CPP	GB/T6672-2001	180±10 micron
Weight liner	GB4669-1995	120±5 g/m ²
Weight of glue	GB4669-1996	28±3 g/m ²
Loop tack	GB/T4582-2002	≥10#
20min peel	FINAT1	≥8 N/25mm
Cohesion	GB/T4851-1998	≥10 h
Release Strenght	FINAT3	0.05-0.15 N/25mm
Dimensional stability	FINAT14	CD≤0.8 MD≤1.0 mm

Available in the online shop:

PL668950	LAMINATED SPIDER PP SANDTEX R-10 180MIC 1,04X50M
PL668960	LAMINATED SPIDER PP SANDTEX R-10 180MIC 1,37X50M
PL668970	LAMINATED SPIDER PP SANDTEX R-10 180MIC 1,52X50M

